

Type: _____

Model: _____

Project: _____

SPECIFICATION SHEET

Ozark Mini Flood Light

SPECIFICATIONS

VOLTAGE: 12 to 24 volts (120V/277V models also available)

HOUSING: Sealed cast aluminum with dark bronze powdercoat (white available with special order). Adjustable hood available.

MOUNTING: Die-cast aluminum knuckle mount. Stainless steel fasteners. Composite mounting stake included.

AGENCY LISTINGS: DLC and UL approved for wet locations and ground mounting.

WARRANTY: Five years.



Ideal for applications such as landscape lighting, small sign lighting, and building accent lighting. 150° (7H × 7V) beam.

Model	490684	490685	490668	490686	490687	490669	490688	490689	490670	490690	490691	490671
Description	LED-MF-7W-2700K-12V	LED-MF-7W-3000K-12V	LED-MF-7W-5000K-12V	LED-MF-12W-2700K-12V	LED-MF-12W-3000K-12V	LED-MF-12W-5000K-12V	LED-MF-20W-2700K-12V	LED-MF-20W-3000K-12V	LED-MF-20W-5000K-12V	LED-MF-40W-2700K-12V	LED-MF-40W-3000K-12V	LED-MF-30W-5000K-12V
Wattage	7W	7W	7W	12W	12W	12W	20W	20W	20W	40W	40W	40W
Lumens	550 lm	600 lm	700 lm	925 lm	880 lm	1200 lm		1700 lm	2000 lm		3400 lm	4000 lm
Efficacy	77 lm/W	88 lm/W	100 lm/W	77 lm/W	67 lm/W	100 lm/W		85 lm/W	100 lm/W		85 lm/W	100 lm/W
Color Temperature	2700K	3000K	5000K	2700K	3000K	5000K	2700K	3000K	5000K	2700K	3000K	5000K
CRI		80	70		80	70		80	70		80	70

DIMENSIONS:

